Annual Indexes

Volume 10—October 1980 to July 1981

1. Subject Index

A

Alkali metal and halide vapors with ceramic materials, Interaction of . 194
Aluminum fluoride to protect fused quartz envelopes from attack by fluorine, Tungsten-fluorine lamps with a passivation layer of 107
Analysis of factors affecting efficacy of high pressure lamps 237
Analytical predictions, Visibility and legibility of exit signs Part I: 24
Applications of luminance data, The potential for design 8
Application, Super high output HID lamps and their 140
Approximation of illuminance, Inverse square law 96

B

Ballast for HPS lamps, An energy efficient solid-state controlled 81
Ballasts during reignition, The interaction of metal halide lamps and 114
Ballasts, Improvement of the luminous efficacy in Sc-Na halide lamps and development of direct retrofit type Sc-Na halide lamps for operation with mercury lamp 133
Brightness meter 52

C

Calculating interior daylight illumination with a programmable hand calculator 219
Calculating point illumination using a programmable pocket calculator .. 149
Calculation of visual comfort probability for luminous sided luminaires, A procedure for the 145
Calculations in unempty rooms, On radiative transfer 120
Calculator, Calculating interior daylight illumination with a programmable hand 219
Calculator, Calculating point illumination using a programmable pocket 149
Calibrating device: Subjective evaluations in a standard environment, A discomfort glare 85
Conserving incandescent lamps, Development of high energy– 214
Conspicuity contours with five-bar grating stimuli, Equal apparent .. 155
Consumption: techniques and results, Monitoring lighting energy 178
Contours with five-bar grating stimuli, Equal apparent conspicuity 155
Contrast, Some issues on the foundation of visibility and task 66
Contrast, Visual performance with realistic methods of changing 164
Controlled ballast for HPS lamps, An energy efficient solid-state 81
Control principles, Equi-visibility lighting 33
Cost-effective visibility-based design procedures for general office lighting 228

D

Daylight illumination with a programmable hand calculator, Calculating interior 219
Design applications of luminance data, The potential for 8
Design procedures for general office lighting, Cost-effective visibility-based 228
Development of direct retrofit type Sc-Na halide lamps for operation with mercury lamp ballasts, Improvement of the luminous efficacy in Sc-Na halide lamps and 133
Development of high energy-conserving incandescent lamps 214
Diagnostics of HID lamps, A direct reading polychromator for real time 40
Diameter fluorescent lamp, Insights into the 26mm 2
Dimming of low pressure sodium and other gas discharge lamps, A method to achieve continuous 245
Direct reading polychromator for real time diagnostics of HID lamps, A . 40
Direct retrofit type Sc-Na halide lamps for operation with mercury lamp ballasts, Improvement of the luminous efficacy in Sc-Na halide lamps and development of 133
Discharge lamps, A method to achieve continuous dimming of low pressure sodium and other gas 245
Discharge lamps, IES approved method for life testing of high intensity 211
Discomfort glare calibrating device: Subjective evaluations in a standard environment, A 85
Discomfort glare from highway lighting 17
Discomfort glare: range effects 74

E

Efficacy in Sc-Na halide lamps and development of direct retrofit type Sc-Na halide lamps for operation with mercury lamp ballasts, Improvement of the luminous 133
Emission spectra, temperature, and voltage measurements of HPS and HPM lamps at start-up 90
Energy-conserving incandescent lamps, Development of high 214
Energy consumption: techniques and results, Monitoring lighting 178
Energy efficient solid-state controlled ballast for HPS lamps, An 81
Environment, A discomfort glare calibrating device: Subjective evaluations in a standard 85
Equal apparent conspicuity contours with five-bar grating stimuli 155
Equi-visibility lighting control principles 33
Evaluations in a standard environment, A discomfort glare calibrating device: Subjective 85
Exit signs Part I: Analytical predictions, Visibility and legibility of .. 24
Exit signs Part II: Experimental results, Visibility and legibility of .. 29
Experimental results, Visibility and legibility of exit signs Part II 29

F

Five-bar grating stimuli, Equal apparent conspicuity contours with . 155
Fluorescent lamp, Insights into the 26mm diameter 2
Fluorescent lamps and other multiport devices, Measurement of power delivered to rapid start 185
Fluorescent lamps, Peak and RMS starting voltage procedure for standard/low energy 204
Fluoride to protect fused quartz envelopes from attack by fluorine, Tungsten-fluorine lamps with a passivation layer of aluminum 107
Fused quartz envelopes from attack by fluorine, Tungsten-fluorine lamps with a passivation layer of aluminum fluoride to protect 107

G

Gas discharge lamps, A method to achieve continuous dimming of low pressure sodium and other 245
Glare calibrating device: Subjective evaluations in a standard environment, A discomfort 85
Glare from highway lighting, Discomfort 17
Glare: range effects, Discomfort 74

H

Halide lamps and ballasts during reignition, The interaction of metal .. 114
Halide lamps and development of direct retrofit type Sc-Na halide lamps for operation with mercury lamps ballasts, Improvement of the luminous efficacy in Sc-Na 133
Halide lamps in E18 outer jackets, Modified NaI-ScI3 metal 130
Halide vapors with ceramic materials, Interaction of alkali metal and ... 194
Hand calculator, Calculating interior daylight illumination with a programmable 219
High energy-conserving incandescent lamps, Development of 214
High intensity discharge lamps, IES approved method for life testing of 211
HID lamps, A direct reading polychromator for real time diagnostics of 40
HID lamps and their application, Super high output 140
High output HID lamps and their application, Super 140
Highway lighting, Discomfort glare from 17

HPS lamps at start-up, Emission spectra, temperature, and voltage measurements of HPS and 90
HPS and HPM lamps at start-up, Emission spectra, temperature, and voltage measurements of 90
HPS lamps, An energy efficient solid-state controlled ballast for 81

I

IES approved method for life testing of high intensity discharge lamps ... 211
Illuminance, Inverse square law approximation of 96
Illumination using a programmable pocket calculator, Calculating point 149
Illumination with a programmable hand calculator, Calculating interior daylight 219
Improvement of the luminous efficacy in Sc-Na halide lamps and development of direct retrofit type Sc-Na halide lamps for operation with mercury lamp ballasts 133
Incandescent lamps, Development of high energy-conserving 214
Insights into the 26mm diameter fluorescent lamp 2
Intensity discharge lamps, IES approved method for life testing of high 211
Interaction of alkali metal and halide vapors with ceramic materials 194
Interaction of metal halide lamps and ballasts during reignition, The ... 114
Interior daylight illumination with a programmable hand calculator, Calculating 219
Inverse square law approximation of illuminance 96
Issues on the foundation of visibility and task contrast, Some 66

L

Lamp, Insights into the 26mm diameter fluorescent 2
Lamps, A direct reading polychromator for real time diagnostics of HID .. 40
Lamps, A method to achieve continuous dimming of low pressure sodium and other gas discharge 245
Lamps and ballasts during reignition, The interaction of metal halide ... 114
Lamps and development of direct retrofit type Sc-Na halide lamps for operation with mercury lamp ballasts, Improvement of the luminous efficacy in Sc-Na halide 133
Lamps and other multi-port devices, Measurement of power delivered to rapid start fluorescent 185
Lamps and their application, Super high output HID 140
Lamps, An energy efficient solid-state controlled ballast for HPS 81
Lamps at start-up, Emission spectra, temperature, and voltage measurements of HPS and HPM 90
Lamps, Development of high energy-conserving incandescent 214
Lamps, IES approved method for life testing of high intensity discharge 211
Lamps in E18 outer jackets, Modified Nal-ScI_3 metal halide. 130
Lamps with a passivation layer of aluminum fluoride to protect fused quartz envelopes from attack by fluorine, Tungsten-fluorine 107
Law approximation of illuminance, Inverse square 96
Legibility of exit signs Part I: Analytical predictions, Visibility and 24
Legibility of exit signs Part II: Experimental results, Visibility and 29
Life testing of high intensity discharge lamps, IES approved method for . 211
Lighting control principles, Equi-visibility 33
Lighting, Cost-effective visibility-based design procedures for general office 228
Lighting, Discomfort glare from highway 17
Lighting energy consumption: techniques and results, Monitoring ... 178
Low pressure sodium and other gas discharge lamps, A method to achieve continuous dimming of ... 245
Luminaire cutoff, Roadway visibility vs 47
Luminaires, A procedure for the calculation of visual comfort probability for luminous sided 145
Luminance data, The potential for design applications of 8
Luminous efficacy in Sc-Na halide lamps and development of direct retrofit type Sc-Na halide lamps for operation with mercury lamp ballast, Improvement of the 133
Luminous sided luminaires, A procedure for the calculation of visual comfort probability for 145

M

Measurement of power delivered to rapid start fluorescent lamps and other multi-port devices 185
Measurements of HPS and HPM lamps at start-up, Emission spectra, temperature, and voltage 90
Mercury lamp ballasts, Improvement of the luminous efficacy in Sc-Na halide lamps and development of direct retrofit type Sc-Na halide lamps for operation with 133
Metal halide lamps and ballasts during reignition, The interaction of 114
Metal halide lamps in E18 outer jackets, Modified Nal-ScI_3 130
Meter, Brightness 52
Method for life testing of high intensity discharge lamps, IES approved ... 211
Method to achieve continuous dimming of low pressure sodium and other gas discharge lamps, A 245
Monitoring lighting energy consumption: techniques and results 178
Multi-port devices, Measurement of power delivered to rapid start fluorescent lamps and other 185

N

Nal-ScI_3 metal halide lamps in E18 outer jackets, Modified 130

O

Office lighting, Cost-effective visibility-based design procedures for general 228
Operation with mercury lamp ballasts, Improvement of the luminous efficacy in Sc-Na halide lamps and development of direct retrofit type Sc-Na halide lamps for 133
Outer jackets, Modifed Nal-ScI_3 metal halide lamps in E18 130

P

Passivation layer of aluminum fluoride to protect fused quartz envelopes from attack by fluorine, Tungsten-fluorine lamps with a 107
Peak and RMS starting voltage procedure for standard/low energy fluorescent lamps 204
Performance with realistic methods of changing contrast, Visual 164
Point illumination using a programmable pocket calculator, Calculating 149
Polychromator for real time diagnostics of HID lamps, A direct reading ... 40
Power delivered to rapid start fluorescent lamps and other multi-port devices, Measurement of 185
Predictions, Visibility and legibility of exit signs Part I: Analytical 24
Pressure sodium and other gas discharge lamps, A method to achieve continuous dimming of low 245
Programmable hand calculator, Calculating interior daylight illumination with a 219
Programmable pocket calculator, Calculating point illumination using a 149

Q

Quartz envelopes from attack by fluorine, Tungsten-fluorine lamps with a passivation layer of aluminum fluoride to protect fused 107

R

Radiative transfer calculations in unempty rooms, On 120
Rapid start fluorescent lamps and other multi-port devices, Measurement of power delivered to 185
Reignition, The interaction of metal halide lamps and ballasts during .. 114
Retrofit type Sc-Na halide lamps for operation with mercury lamp ballasts, Improvement of the luminous efficacy in Sc-Na halide lamps and development of direct 133
RMS starting voltage procedure for standard/low energy fluorescent lamps, Peak and 204
Roadway visibility vs luminaire cutoff 47
Rooms, On radiative transfer calculations in unempty 120

S

Sc-Na halide lamps and development of direct retrofit type Sc-Na halide lamps for operation with mercury lamp ballasts, Improvement of the luminous efficacy in 133
Signs Part I: Analytical predictions, Visibility and legibility of exit 24
Signs Part II: Experimental results, Visibility and legibility of exit 29
Sodium and other gas discharge lamps, A method to achieve continuous dimming of low pressure 245
Solid-state controlled ballast for HPS lamps, An energy efficient 81
Spectra, temperature, and voltage measurements of HPS and HPS lamps at start-up, Emission 90
Square law approximation of illuminance, Inverse 96

Standard environment, A discomfort glare calibrating device: Subjective evaluations in a 85
Start-up, Emission spectra, temperature, and voltage measurements of HPS and HPM lamps at 90
Subjective evaluations in a standard environment, A discomfort glare calibrating device: 85
Super high output HID lamps and their application 140

T

Task contrast, Some issues on the foundation of visibility and 66
Techniques and results, Monitoring lighting energy consumption: 178
Temperature, and voltage measurements of HPS and HPM lamps at start-up, Emission spectra 90
Testing of high intensity discharge lamps, IES approved method for life 211
Time diagnostics of HID lamps, A direct reading polychromator for real 40
Transfer calculations in unempty rooms, On radiative 120
Tungsten-fluorine lamps with a passivation layer of aluminum fluoride to protect fused quartz envelopes from attack by fluorine 107

U

Unempty rooms, On radiative transfer calculations in 120

V

Visibility and legibility of exit signs Part I: Analytical predictions 24
Visibility and legibility of exit signs Part II: Experimental results 29
Visibility and task contrast, Some issues on the foundation of 66
Visibility-based design procedures for general office lighting, Cost-effective 228
Visibility vs luminaire cutoff, Roadway 47
Visual comfort probability for luminous sided luminaires, A procedure for the calculation of 145
Visual performance with realistic methods of changing contrast 164
Voltage measurements of HPS and HPM lamps at start-up, Emission spectra, temperature, and 90

2. Author Index

B

Baba, K.—Improvement of the luminous efficacy in Sc-Na halide lamps and development of direct retrofit type Sc-Na halide lamps for operation with mercury lamp ballasts .. 133
Bennett, C. A.—Discomfort glare: range effects 74
Berman, S.—Cost-effective visibility-based design procedures for general office lighting 228
Bernecker, C. A.—The potential for design applications of luminance data 8
Blamey, C.—Discomfort glare from highway lighting 17
Bodinger, D.—Discomfort glare from highway lighting 17
Brett, J.—Development of high energy-conserving incandescent lamps 214

C

Chen, E.—Brightness meter 52
Clear, R.—Calculating interior daylight illumination with a programmable hand calculator 219
Clear, R.—Cost-effective visibility-based design procedures for general office lighting 228

D

de Groot, J. J.—Insights into the 26mm diameter fluorescent lamp 2
Denneman, J. W.—Insights into the 26mm diameter fluorescent lamp . 2
Di Fraia, L.—A method to achieve continuous dimming of low pressure sodium and other gas discharge lamps 245
DiLaura, D.—A procedure for the calculation of visual comfort probability for luminous sided luminaires 145
DiLaura, D.—On radiative transfer calculations in unempty rooms ... 120

E

Elms, R. T.—An energy efficient solid-state controlled ballast for HPS lamps 81
Engel, J. C.—An energy efficient solid-state controlled ballast for HPS lamps 81
Ewing, J. L.—Roadway visibility vs luminaire cutoff 47

F

Fitzpatrick, J. R.—Tungsten-fluorine lamps with a passivation layer of aluminum fluoride to protect fused quartz envelopes from attack by fluorine 107
Fontana, R.—Development of high energy-conserving incandescent lamps 214

G

Goddard, V. W.—Tungsten-fluorine lamps with a passivation layer of aluminum fluoride to protect fused quartz envelopes from attack by fluorine 107

H

Hammer, E. E.—Peak and RMS starting voltage procedure for standard/low energy fluorescent lamps 204
Hanson, R. E.—An energy efficient solid-state controlled ballast for HPS lamps 81
Hing, P.—Interaction of alkali metal and halide vapors with ceramic materials 194
Hirayama, C.—Emission spectra, temperature, and voltage measurements of HPS and HPM lamps at start-up 90

J

Jack, A. G.—Insights into the 26mm diameter fluorescent lamp 2
Jung, F. W.—Discomfort glare from highway lighting 17

K

Kaiser, P. K.—Discomfort glare from highway lighting 17
Kanoh, T.—Super high output HID lamps and their application 140
Keeffe, W. M.—A direct reading polychromator for real time diagnostics of HID lamps 40
Kulkarni, A. D.—Modified NaI-ScI_3 metal halide lamps in E18 outer jackets 130

L

Levy, A. W.—Monitoring lighting energy consumption: techniques and results 178
Ligthart, F. A. S.—Insights into the 26mm diameter fluorescent lamp . 2
Lulla, A. B.—Discomfort glare: range effects 74

M

McCloskey, M. M.—A procedure for the calculation of visual comfort probability for luminous sided luminaires 145
McNelis, J. F.—A discomfort glare calibrating device: Subjective evaluations in a standard environment 85
Morton, E. W.—Brightness meter .. 52
Murdoch, J. B.—Inverse square law approximation of illuminance 96

N

Ngai, P. Y.—Some issues on the foundation of visibility and task contrast 66

O

Orthwein, W. C.—Calculating point illumination using a programmable pocket calculator 149

P

Partlow, W. D.—The interaction of metal halide lamps and ballasts during reignition 114
Pierpoint, W.—Equi-visibility lighting control principles 33

R

Rachko, D.—Brightness meter 52
Reagan, J. A.—Visibility and legibility of exit signs Part I: Analytical predictions 24

Reagan, J. A.—Visibility and legibility of exit signs Part II: Experimental results 29
Rea, M. S.—Visual performance with realistic methods of changing contrast 164
Retzer, T. C.—Modified NaI-ScI_3 metal halide lamps in E18 outer jackets 130
Robertson, W.—Monitoring lighting energy consumption: techniques and results 178
Roberts, V. D.—Measurement of power delivered to rapid start fluorescent lamps and other multi-port devices 185
Rothwell, H. L. Jr.—A direct reading polychromator for real time diagnostics of HID lamps 40

S

Saito, M.—Improvement of the luminous efficacy in Sc-Na halide lamps and development of direct retrofit type Sc-Na halide lamps for operation with mercury lamp ballasts .. 133
Sell, H. G.—Modified NaI-ScI_3 metal halide lamps in E18 outer jackets . 130
Schooley, L. C.—Visibility and legibility of exit signs Part I: Analytical predictions 24
Schooley, L. C.—Visibility and legibility of exit signs Part II: Experimental results 29
Shinjoh, K.—Super high output HID lamps and their application 140
Singleton, J. H.—Emission spectra, temperature, and voltage measurements of HPS and HPM lamps at start-up 90

T

Thornton, W. A.—Brightness meter 52
Tibbott, R. L.—Equal apparent conspicuity contours with five-bar grating stimuli 155
Tsuchihaski, M.—Improvement of the luminous efficacy in Sc-Na halide lamps and development of direct retrofit type Sc-Na halide lamps for operation with mercury lamp ballasts 133

W

Walsh, P.—Development of high energy-conserving incandescent lamps 214
Watanabe, K.—Improvement of the luminous efficacy in Sc-Na halide lamps and development of direct retrofit type Sc-Na halide lamps for operation with mercury lamp ballasts 133
Waymouth, J. F.—Analysis of factors affecting efficacy of high pressure sodium lamps 237
Wolfe, A. L.—Emission spectra, temperature, and voltage measurements of HPS and HPM lamps at start-up 90
Wyner, E. F.—Analysis of factors affecting efficacy of high pressure sodium lamps 237

Y

Yonemura, G. T.—Equal apparent conspicuity contours with five- bar grating stimuli 155